

更改 REV	出 图 日 期 DATE	设 变 内 容 MODIFICATION	修 改 DRAWN
	2010/08/10		

SPECIFICATIONS

1. ELECTRICAL:

UL APPLICATIONS: 250 VOLTS AC MAX., AT 2 AMPS.
DIELECTRIC WITHSTANDING VOLTAGE: 500 VOLTS AC.
INSULATION RESISTANCE: 100 M Ω .
TERMINATION: RESISTANCE 20m Ω MAX AFTER ENVIRONMENTAL TESTING.







2. MECHANICAL:

CABLE-TO-PLUG TENSILE STRENGTH: ~~2000~~ND MIN.
DURABILITY: 200 MATING CYCLES.

3. MATERIAL & FINISH:

HOUSING: POLYCARBONATE, UL94V-0 OR UL94V-2.
COLOR: TRANSPARENT OR OTHER COLOR ARE AVAILABLE.
CONTACT BLADE: COPPER ALLOY.
CONDUCTOR: STRANDED & SOLID WIRE, 24AWG, 26 AWG.
GOLD PLATING: 3u"~50u", ARE AVAILABLE.

ITEM: 21.17.3062-50

BLADE:	E		Y		Z		A		AB		YL		ZL		
Drawing															
Mark															
GOLD PLATING	3Mu"		3u"		6u"		15u"		30u"		50u"		CABLE TYPE	ROUND	FLAT
Mark											Mark				

客户用产品图

Rotronic Co., Ltd.				
DIMENSION IN mm (Inch) TOLERANCE UNLESS OTHERWISE SPECIFIED		材 质 MATERIAL PC	图 号 DWG NO. PLUG-031(2.6)	
.X $\pm$ 0.20	.X $^{\circ}$ $\pm$ 5 $^{\circ}$	名称 TITLE 21.17.3062		
.XX $\pm$ 0.10	.XX $^{\circ}$ $\pm$ 2 $^{\circ}$			
审 核 APPROVAL	核 对 CHECKED	制 图 DRAWN LiWenjuan	比例 SCALE 5/2	张数 SHEET 1/1
		角法 PROJ. 	更改 REV A	

ST-DR-009A

