




PIN ASSIGNMENT:

USB C TYPE M(P1)	USB C TYPE FM(P2)
A1,A12,B1,B12	A1,A12,B1,B12
A2	A2
A3	A3
A4,A9,B4,B9	A4,A9,B4,B9
A5	A5
A6	A6
A7	A7
A8	A8
A10	A10
A11	A11
B2	B2
B3	B3
B5	B5
B6	B6
B7	B7
B8	B8
B10	B10
B11	B11
SHELL	SHELL

NOTE:

- 1.Electrical properties:
- 1.ALL COMPONENTS ARE RoHS COMPLIANT.

2.100% OPEN AND SHORT TEST.

3.CONDUCTOR RESISTANCE:3 OHMS

4.INSULATION RESISTANCE:10 MEGOHMS.

5.HI-POT:DC200V/0.01S
2. ROHS 2.0 and REACH

MATERIAL LIST

					Name	ROLINE USB 3.1 Type C Adapter, C-C, M/F, 90° Angled, white			
					DRAW No.		NAME	12.03.2996	
③	OUTER MOLD	PVC CLOLR:WHITE	1				MAPE	TOLERANCE	
②	CONNECTOR	USB3.1 TYPE C FEMALE ,NICKEL PLATED SHELL	1					X. ±1.00 X.X ±0.50	
①	CONNECTOR	USB3.1 TYPE C MALE ,NICKEL PLATED SHELL	1				DRAW BY	SCALE	MM
No.	PART NAME	DESCRIPTION	QTY					PAGE	1/1