


ROHS-COMPLIANT


LTR	REV.	DESCRIPTION	DATE
Δ*4	II	EDIT PACKING ADD LENGTH,P/N	05/03/10'

USB 3.0 A/M 9PIN
INS:BLUE(PT 300C)




L ± T


USB 3.0 A/F 9PIN
INS:BLUE(PT 300C)



TUSB-0189



TUSB-0193



NOTE:

1.CABLE: UL-2725 [#28(7/0.127 T.C)×1P INS:Foam-PE+D.W(7/0.127 T.C)

+AL/MY+Hot-melt-Mylar]×2C+#28(7/0.127 T.C)×1P INS:Polyolefin
+#28(7/0.127 T.C)×2C INS:Polyolefin+AL/MY+B.D(85%)

PVC JACKET; OD:5.2±0.15mm COLOR:BLACK(NK-K01) REV 3.0.

2.CONNECTOR:

P1: USB 3.0 A TYPE MALE 9PIN CONTACT:30u",SHELL:NI-PLATED.

P2 :USB 3.0 A TYPE FEMALE 9PIN CONTACT:30u",SHELL:NI-PLATED.

3.HOOD:MOLDED TYPE,PVC 45P , COLOR:BLACK(NK-K01).

4.ELECTRICAL TEST:

(1)100% OPEN SHORT & MIS WIRE TEST.

(2)CONTACT RESISTANCE 3 ohm Max .

(3)INSULATION RESISTANCE 10M ohm Min .

Δ 5.PACKING:<1>EACH PC / ROLINE SMALL HEADER CARD

<2>EACH PC / ROLINE BIG HEADER CARD

50 PCS / CARTON

PIN OUT		CABLE FUNCTION	
P1		P2	
1	RED	1	PWR
2	WHITE	2	UTP_D-
3	GREEN	3	UTP_D+
4	BLACK	4	GND_PWRrt
5	BLUE	5	SDP1-
6	YELLOW	6	SDP1+
7	D.W	7	SDP1_Drain & SDP2_Drain
8	PURPLE	8	SDP2-
9	ORANGE	9	SDP2+
SHELL	B.D	SHELL	

Tolerance Inch M/M		
.X	.015	.30
.XX	.010	.10
.XXX	.005	.05

Title		
USB 3.0 A/M - A/F CABLE		

170-3781-3	11.02.8977	800	10	<1>
170-3781-2		3000	30	<2>
170-3781-1	11.02.8978	1800	30	<1>
DWG	P/N	L(mm)	T(mm)	PACKING

FANNIE 05/03/10'					Customer P/N	
Check	App'd			Customer: T-RAG		
	Scale	NONE	Units	M/M	Third Angle Projection	
Engr	Dwg No. 170-3781			REF: II	Sheet. 1/1	